


Network Camera

HV-IP-B6481E 8MP 4K Network Camera



Features

- ✓ H.265+/H.265/H.264+/H.264 coding
- ✓ Max.resolution: 8MP (3840 × 2160)
- ✓ ICR auto switch, true day / night vision
- ✓ 3D DNR, true WDR, HLC, BLC, smart IR and ROI coding
- ✓ Lens distortion correction supported
- ✓ 30~50m IR night view distance
- ✓ 1CH audio input
- ✓ Built-in micro SD card slot, up to 256GB
- ✓ DC12V/PoE power supply
- ✓ Support three streams
- ✓ IP 67
- ✓ Support mobile surveillance by smart phones with iOS and Android OS
- ✓ Intelligent analytics

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

Technical Specification

HV-IP-B6481E



Model	HV-IP-B6481E	
Camera		
Image Sensor	1 / 2.8" CMOS	
Image Size	3840×2160	
Electronic Shutter	1 s ~ 1 / 100000 s	
Iris Type	Fixed Iris	
Min. Illumination	0.05 lux @ F1.4, AGC ON; 0 lux with IR, 0.06 lux @ F1.6, AGC ON; 0 lux with IR, 0.1lux@F2.0, AGC ON; 0 lux with IR	
Lens	2.8 mm @F1.6, Horizontal FoV:109.7°; Vertical FoV:77.2°; Diagonal FoV:116.9° 3.6 mm @F2.0, Horizontal FoV: 90.6°; Vertical FoV:59.2°; Diagonal FoV:98.4°	2.8~12mm@F1.4, Horizontal FoV: 104.7°~32.5°; Vertical FoV:72.2°~ 18.6°; Diagonal FoV:112.2°~37°
Focus	Fixed	Motorized
Lens Mount	M12	Ø14
Day& Night	ICR	
Wide Dynamic Range	120dB	
BLC	Yes	
HLC	Yes	
Defog	Yes	
Digital NR	3D DNR	
Angle Adjustment	Pan: 0°~360°; Tilt:0°~90°; Rotation: 0°~360°	
Image		
Video Compression	H.265+ / H.265 / H.264+ / H.264	
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile	
Resolution	8MP (3840 × 2160), 6MP(3072 × 2048),5MP(2592 × 1944), 4MP (2560 × 1440), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240	
Main Stream	60Hz : 8MP/6MP(1~20fps), 5MP/4MP/1080P(1~30fps) 50Hz : 8MP/6MP(1~20fps), 5MP/4MP/1080P(1~25fps)	
Sub Stream	720P/D1/CIF/480 × 240(60Hz: 1~30fps; 50Hz: 1~25fps)	
Third Stream	D1/CIF/480 × 240 (60Hz: 1~30fps; 50Hz: 1~25fps)	
Bit Rate	64 Kbps ~ 12 Mbps	
Bit Rate Type	VBR / CBR	
Audio Compression	G711A / U	
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, etc. adjustable through client software or web browser	
ROI	3 ROI, Each ROI to be configured separately	

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

AAA SECURITY SOLUTIONS: 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034

SALES: 011-47097440 | **SALES EMAIL:** INFO@HAWKVISIONINDIA.COM | **SUPPORT EMAIL:** SUPPORT@HAWKVISIONINDIA.COM

Technical Specification

HV-IP-B6481E



Interfaces	
Network	RJ45
Video Output	No
Audio	1CH audio input
Storage	Built-in micro SD card slot; up to 256GB
Reset	Yes
Functions	
Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGMP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection; SD card error; SD card full
Intelligent Analytics	Scene change, video blur detection, video color cast detection, line crossing detection, intrusion detection
General Function	Watermark, IP address filtering, video mask, heartbeat, password protection, image distortion correction, etc.
PoE	Yes (IEEE802.3af)
IR Distance	30~50 m
Protection Grade	IP 67
Others	
Power Supply	DC12V/PoE
Power Consumption	< 10W
Operating Environment	- 30 °C ~ 60 (-22 °C ~ 140°F) Humidity: less than 95 % non condensing
Dimensions (mm)	217.8 × 80.5 × 80.3
Weight (net)	Approx. 0.665KG
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006)

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

AAA SECURITY SOLUTIONS: 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034

SALES: 011-47097440 | **SALES EMAIL:** INFO@HAWKVISIONINDIA.COM | **SUPPORT EMAIL:** SUPPORT@HAWKVISIONINDIA.COM