

Full Color AHD Camera

HV-AHD-B3420T-SH-A 2MP Full Color AHD Bullet Camera





Features

- ✓ 1/2.8" 2 MP CMOS Sensor
- Effective Pixels : 1920x1080
- Illumination : 0.01Lux @ F1.2, 0.015 lux @ F1.4
- 2 pcs Smart Warm Light
- ✔ Auto ICR/3D DNR/Color/Day/Night
- ✓ IR Distance 15 to 20 Mtr.
- ✓ 3.6/6 mm optional
- ✔ 6KV Surge Protection
- In build audio

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

www.hawkvisionindia.com



CCTV CAMERAS | NVR & DVR SERIES | ATTENDANCE MACHINES & ACS | VDP SERIES



Technical Specification ну-анд-вз420т-ян-а



Model	HV-AHD-B3420T-SH-A	
Image sensor	1/2.8" 2 MP CMOS Sensor	
Signal System	PAL/NTSC	
Effective Pixels	1980 (H) × 1080 (V)	
Frequency	50 Hz (PAL) / 60 Hz (NTSC)	
Video Frame Rate	1080p @25fps	
Horizontal Resolution	2 Megapixel	
Minimum Illumination	Color : 0.01Lux @ F1.2, 0.015 lux @ F1.4; B&W: 0 Lux at IR on	$\left(0\right) $
Signal to Noise	> 62 Db	
Gain Control	Auto	
White Balance	Auto (2000K to 10000K)	
DNR	Inbuilt 3D DNR (Digital Noise Reduction) circuit	
Auto Iris	DC Drive	
Gamma Correction	0.45	
Sync System	Internal	
Audio	In build mic	
Lens		
Lens Type	3.6mm lens	
Lens Mount	M12	
Focus	Fixed	
Day/Night Functionality		
Day & Night	Full Color	
	Full Color High performance Mechanical IR Cut Filter with auto switch	
Day & Night		
Day & Night IR Cut	High performance Mechanical IR Cut Filter with auto switch	
Day & Night IR Cut IR Source	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control	
Day & Night IR Cut IR Source IR Range	High performance Mechanical IR Cut Filter with auto switchHigh performance 2 nos. SMART Warm light with intensity ControlUp to 20 Mtrs	
Day & Night IR Cut IR Source IR Range IR Life	High performance Mechanical IR Cut Filter with auto switchHigh performance 2 nos. SMART Warm light with intensity ControlUp to 20 Mtrs	
Day & Night IR Cut IR Source IR Range IR Life Interface	 High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 	
Day & NightIR CutIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower Requirement	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 1 Analog AHD Video output	
Day & NightIR CutIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower RequirementPower Consumption	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 1 Analog AHD Video output Standard DC Jack	
Day & NightIR CutIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower RequirementPower ConsumptionEnvironmental	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 1 Analog AHD Video output Standard DC Jack 12 VDC ± 10% Max 6 W with IR on	
Day & NightIR CutIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower RequirementPower ConsumptionEnvironmentalEnclosure	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 1 Analog AHD Video output Standard DC Jack 12 VDC ± 10% Max 6 W with IR on IP 66 Weather proof	
Day & NightIR CutIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower RequirementPower ConsumptionEnvironmentalEnclosureMounting bracket	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 1 Analog AHD Video output Standard DC Jack 12 VDC ± 10% Max 6 W with IR on IP 66 Weather proof Optional	
Day & NightIR CutIR SourceIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower RequirementPower ConsumptionEnvironmentalEnclosureMounting bracketOperating Temperature	High performance Mechanical IR Cut Filter with auto switchHigh performance 2 nos. SMART Warm light with intensity ControlUp to 20 Mtrs40000 operation hours1 Analog AHD Video outputStandard DC Jack12 VDC ± 10%Max 6 W with IR onIP 66 Weather proofOptional-20°C to + 60°C	
Day & NightIR CutIR SourceIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower RequirementPower ConsumptionEnvironmentalEnclosureMounting bracketOperating TemperatureOperating Humidity	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 1 Analog AHD Video output Standard DC Jack 12 VDC ± 10% Max 6 W with IR on IP 66 Weather proof Optional	
Day & NightIR CutIR CutIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower RequirementPower ConsumptionEnvironmentalEnclosureMounting bracketOperating TemperatureOperating HumidityMechanical	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 1 Analog AHD Video output Standard DC Jack 12 VDC ± 10% Max 6 W with IR on IP 66 Weather proof Optional -20°C to + 60°C 95% or less (non-condensing)	
Day & NightIR CutIR CutIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower RequirementPower ConsumptionEnvironmentalEnclosureMounting bracketOperating TemperatureOperating HumidityMechanicalColor / Material	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 1 Analog AHD Video output Standard DC Jack 12 VDC ± 10% Max 6 W with IR on IP 66 Weather proof Optional -20°C to + 60°C 95% or less (non-condensing) White / Plastic	
Day & NightIR CutIR CutIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower RequirementPower ConsumptionEnvironmentalEnclosureMounting bracketOperating TemperatureOperating HumidityMechanicalColor / MaterialDimensions	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 1 Analog AHD Video output Standard DC Jack 12 VDC ± 10% Max 6 W with IR on -20°C to + 60°C 95% or less (non-condensing) White / Plastic L(154mm) x H(71mm) x W(71mm)	
Day & NightIR CutIR CutIR SourceIR RangeIR LifeInterfaceVideo OutputPower InputPower RequirementPower ConsumptionEnvironmentalEnclosureMounting bracketOperating TemperatureOperating HumidityMechanicalColor / Material	High performance Mechanical IR Cut Filter with auto switch High performance 2 nos. SMART Warm light with intensity Control Up to 20 Mtrs 40000 operation hours 1 Analog AHD Video output Standard DC Jack 12 VDC ± 10% Max 6 W with IR on IP 66 Weather proof Optional -20°C to + 60°C 95% or less (non-condensing) White / Plastic	

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

AAA SECURITY SOLUTIONS: 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034 SALES: 011-47097440 | SALES EMAIL: INFO@HAWKVISIONINDIA.COM | SUPPORT EMAIL: SUPPORT@HAWKVISIONINDIA.COM

