

Digital Video Recorder

HV-D5100-4HL 1080P Hybrid DVR









DDNS







AUDIO

NETWORK

.1.

PTZ





MOBILE







CMS

Features

- ✓ 4 CH TVI / AHD/CVI 1080P/1080P Lite/720P/WD1 video input
- ✓ 4 CH DVR supports 2 CH 3MP /1080P / 960P /720P IP video input by default
- ✓ 4 CH DVR supports 4 CH analog input switched to IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- ✓ Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- ✓ Multi-mode recording: manual / timed / motion / Al recording
- ✓ Playback: 4 CH simultaneously playback
- ✓ Search: time slice, time, event, tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access DHCP, DDNS, PPPoE network protocol
- ✓ Remote control via Web or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- ✓ Authorization management, log review and device status review
- ✓ Supports 1080P output, true high resolution display
- ✓ Supports PTZ preset and auto cruise, up to 255 presets and 8 cruises
- ✓ Supports NAT function and QRCode scanning by mobile phones
- ✔ Powerful mobile surveillance by smart phones with iOS and Andriod OS

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.





Technical Specification HV-D5100-4HL



Model		HV-D5100-4HL
System	OS	Embedded Linux
Video	Analog Input	BNC × 4
	Resolution	TVI/ AHD/CVI : 1080P/ 1080PLite/ 720P/ WD1
	IP Input	2CH (Up to 6CH)
	Total Input	6CH
	Output	HDMI × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768
	Multi-screen Display	1/4/6/8/9
Audio	Input/ Output	RCA \times 1/ RCA \times 1 (linear, 600Ω)
	Two-way Audio	Take up channel one audio input
Standard	Video Compression	H.264/H.265
	Audio Compression	G.711(U/A)
Record	Resolution	1080P Lite/ 720P/ WD1
	Frame Rate	Analog Channel: 1080P Lite/720P/WD1 : 25fps (PAL)/30fps (NTSC) IP Channel: 25fps (PAL)/30fps (NTSC)
	Bitrate	32Kbps ~ 4Mbps
IP Input	Resolution	Up to 3MP@30fps
Playback	Playback	4 CH
	Search	Time slice/time/event/tag search
	Smart Search	Highlight colors to display the camera record in a certain period of time, different colors refer to different record events
	Function	Play, pause, FF, FB, digital zoom, etc.
Alarm	Input/Output	No
Network	Interface	RJ 45 100Mbps × 1
	Protocol	TCP/IP, PPPoE, DHCP,DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPs, ONVIF
	Incoming/Outgoing Bandwidth	10Mbps (Max. 30Mbps)/ 30Mbps
	Client Connection	Max. 5 users access
Mobile Device	OS	iOS, Andriod
Storage	HDD	SATA × 1, up to 6TB
Backup	Local Backup	U disk, USB mobile HDD
	Network Backup	Yes
Port	RS 485	No
	USB	USB 2.0 × 2
	Remote Controller	No
Others	Power Supply	DC12V / 1.5A
	Consumption	≤5W(without HDD)
	Dimensions (mm)	255× 222× 42(W × D × H)
	Working Environment	-10~50°C, 10%~9% humidity
	Certificate	CE, FCC
	Environment Protection	Complies with Directive EU RoHS, WEEE, REACH

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

AAA SECURITY SOLUTIONS: 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034
SALES: 011-47097440 | SALES EMAIL: INFO@HAWKVISIONINDIA.COM | SUPPORT EMAIL: SUPPORT@HAWKVISIONINDIA.COM

