


## Network Camera

# HV-IP-B6422E

## 2MP IR Bullet Camera



## Features

- ✓ 2MP ( 1920 × 1080 ) H.265 coding
- ✓ Max. resolution: 1920 × 1080
- ✓ ICR auto switch, true day / night
- ✓ 3D DNR, digital WDR, HLC, BLC, Defog and ROI coding
- ✓ 30~50m IR night view distance
- ✓ 1CH audio input
- ✓ Built-in micro SD card slot, up to 128GB
- ✓ DC12V/PoE power supply
- ✓ IP 67 ingress protection
- ✓ Support three streams
- ✓ Support mobile surveillance by smart phones and tablet PCs with iOS or Android OS
- ✓ Intelligent analytics

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

[www.hawkvisionindia.com](http://www.hawkvisionindia.com)



# Technical Specification

## HV-IP-B6422E



<b>Model</b>	<b>HV-IP-B6422E</b>	
<b>Camera</b>		
<b>Image Sensor</b>	1 / 2.8" CMOS	
<b>Image Size</b>	1920 × 1080	
<b>Electronic Shutter</b>	1 s ~ 1 / 100000 s	
<b>Iris Type</b>	Fixed Iris	
<b>Min. Illumination</b>	0.0035 lux@F1.2,AGC ON; 0 lux with IR 0.009 lux@F1.6,AGC ON; 0 lux with IR	
<b>Lens</b>	2.8 mm @F1.6, H.FoV: 105.4°,V.FoV:72.9°, D.FoV:112.8° 3.6 mm @F1.6, H.FoV: 87.3°, V.FoV:56.5°, D.FoV:95.2°	2.8~12mm@F1.4, H.FoV: 88-34.8°; V. FoV: 57-20°; D. FoV: 96-39.6°
<b>Focus</b>	Fixed	Manual
<b>Lens Mount</b>	M12	Ø14
<b>Wide Dynamic Range</b>	Digital WDR	
<b>BLC</b>	Yes	
<b>HLC</b>	Yes	
<b>Digital NR</b>	3D DNR	
<b>Angle Adjustment</b>	Pan: 0°~360°; Tilt:0°~90°; Rotation: 0°~360°	
<b>Image</b>		
<b>Video Compression</b>	H.265 / H.264	
<b>H.265 CompressionStandard</b>	Main Profile@Leve4.1 High Tier	
<b>Resolution</b>	1080P ( 1920 × 1080 ), 720P ( 1280 × 720 ), D1, CIF, 480 × 240	
<b>Main Stream</b>	60Hz : 1080P( 1 ~ 30fps ) / 720P( 1 ~ 30fps ) 50Hz : 1080P( 1 ~ 25fps ) / 720P( 1 ~ 25fps )	
<b>Sub Stream</b>	60Hz : D1/CIF (1~30fps); 50HZ: D1/CIF (1~25fps)	
<b>Third Stream</b>	60Hz : D1/CIF/480×240 (1~30fps); 50HZ: D1/CIF/480×240 (1~25fps)	
<b>Bit Rate</b>	64 Kbps ~ 6Mbps	
<b>Bit Rate Type</b>	VBR / CBR	
<b>Audio Compression</b>	G711A / U	
<b>Image Settings</b>	ROI, Saturation, Brightness, Hue, Contrast,Wide Dynamic, Defog, Sharpness, NR, etc. adjustable through client software or web browser	
<b>ROI</b>	Each ROI to be configured separately	
<b>Interfaces</b>		
<b>Network</b>	RJ 45	
<b>Audio</b>	1CH audio input	
<b>Storage</b>	Built-in micro SD card slot; up to 128GB	
<b>Reset</b>	Yes	

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

**AAA SECURITY SOLUTIONS:** 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034

**SALES:** 011-47097440 | **SALES EMAIL:** INFO@HAWKVISIONINDIA.COM | **SUPPORT EMAIL:** SUPPORT@HAWKVISIONINDIA.COM

# Technical Specification

## HV-IP-B6422E



Functions	
<b>Remote Monitoring</b>	Web browsing, CMS remote control
<b>Online Connection</b>	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
<b>Network Protocol</b>	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, 802.1x, FTP, UPnP, HTTPs, HTTP, QoS
<b>Interface Protocol</b>	ONVIF
<b>Storage</b>	Network remote storage; micro SD card storage
<b>Smart Alarm</b>	Motion detection, SD card full, SD card error
<b>Intelligent Analytics</b>	Video blur detection, scene change detection, line crossing detection, region intrusion detection and object removal detection (object left/missing)
<b>General Function</b>	Watermark, IP address filtering, video mask, heartbeat, illegal login lock
<b>PoE</b>	Yes, IEEE802.3af
<b>IR Distance</b>	30 ~ 50 m
<b>Ingress Protection</b>	IP 67
Others	
<b>Power Supply</b>	DC12V / PoE
<b>Power Consumption</b>	< 7W
<b>Operating Environment</b>	- 30 °C ~ 60 °C (-22°F~140°F) Humidity: less than 95 % (non-condensing)
<b>Dimensions ( mm )</b>	217.8 × 80.5 × 80.3
<b>Weight ( net )</b>	Approx. 0.65KG
<b>Installation</b>	Ceiling mounting; Wall mounting
<b>Certificate</b>	CE, FCC
<b>Environmental Protection</b>	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

**AAA SECURITY SOLUTIONS:** 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034

**SALES:** 011-47097440 | **SALES EMAIL:** INFO@HAWKVISIONINDIA.COM | **SUPPORT EMAIL:** SUPPORT@HAWKVISIONINDIA.COM