

Network Camera

HV-IP-D6525ES-A-VFM 2MP IR Starlight Dome Camera





DETECTION

Features

- ✓ 2MP (1920 × 1080) H.265 full real time coding
- ✓ Max. resolution: 1920 × 1080; ICR auto switch, true day / night
- ✓ 30 ~ 50m IR night view distance
- ✓ Starlight
- ✓ 3D DNR, Digital WDR, HLC, BLC and Defog
- ✓ ROI coding
- ✔ Built-in micro SD card slot, up to 128GB
- ✔ DC12V/PoE power supply
- IP67 ingress protection
- Support dual streams
- ✔ Support mobile surveillance by smart phones with iOS and Android OS
- ✓ Intelligent Analytics: video blur detection, line crossing detection, intrusion detection

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

www.hawkvisionindia.com



CCTV CAMERAS | NVR & DVR SERIES | ATTENDANCE MACHINES & ACS | VDP SERIES



Technical Specification HV-IP-D6525ES-A-VFM



| Model | HV-IP-D6525ES-A-VFM | |
|---------------------------|--|-----------------|
| Camera | | |
| Image Sensor | 1 / 2.8" CMOS | |
| Image Size | 1920 × 1080 | |
| Electronic Shutter | 1 s ~ 1 / 100000 s | |
| Iris Type | Fixed Iris | |
| Min. Illumination | 0.007 lux@F2.0,AGC ON; 0 lux with IR0.0028 lux@F1.2,AGC ON; 0 lux with IR | (0) |
| Lens | 2.8~12mm @F1.4,H.FoV: 91°~37.5°; V.FoV:51°~20.5°; D.FoV:96°~42.0° | |
| Lens Mount | Φ14 | |
| Wide Dynamic Range | Digital WDR | |
| BLC | Yes | |
| HLC | Yes | |
| Defog | Yes | |
| Digital NR | 3D DNR | |
| Angle Adjustment | Pan: 0°~360°; Tilt:0°~80°; Rotation: 0°~360° | |
| Image | | |
| Video Compression | Main stream:H.265 / H.264; Sub stream:H.265 / H.264 / MJPEG | |
| H.264 CompressionStandard | Baseline Profile/Main Profile/High Profile | |
| Resolution | 1080P (1920 \times 1080), 720P (1280 \times 720), D1, CIF, 480 \times 240 | |
| Main Stream | 60Hz : 1080P(1 ~ 30fps) / 720P(1 ~ 30fps) 50Hz : 1080P(1 ~ 25fps) / 720P(1 ~ 25fps) | |
| Sub Stream | 60Hz : D1/CIF 480x240 (1~30fps); 50HZ: D1/CIF 480x240 (1~25fps) | |
| Bit Rate | 128 Kbps ~ 6 Mbps | |
| Bit Rate Type | VBR / CBR | |
| Audio Compression | G711A / U | |
| Image Settings | ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, etc. adj client software or web browser | ustable through |
| ROI | Each ROI to be configured separately | |
| Interfaces | | |
| Network | RJ 45 | |
| Video Output | NO | |
| Audio | 1CH built-in MIC | |
| Storage | Built-in micro SD card slot; up to 128GB | |
| Reset | Yes | |

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

AAA SECURITY SOLUTIONS: 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034 SALES: 011-47097440 | SALES EMAIL: INFO@HAWKVISIONINDIA.COM | SUPPORT EMAIL: SUPPORT@HAWKVISIONINDIA.COM



Technical Specification HV-IP-D6525ES-A-VFM



| Functions | | |
|--------------------------|---|--|
| Remote Monitoring | Web browsing,CMS remote control | |
| Online Connection | Support simultaneous monitoring for up to 3 users;Support multi-stream real time transmission | |
| Network Protocol | UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, 802.1x, SMTP, FTP,UPnP, HTTPs, HTTP, QoS | |
| Interface Protocol | ONVIF | |
| Storage | Network remote storage; micro SD card storage | |
| Intelligent Analytics | Video blur detection, intrusion detection and line crossing detection | |
| Smart Alarm | Motion detection, SD card error, SD card full | |
| General function | Watermark, IP address filtering, video mask, heartbeat, illegal login lock | |
| PoE | Yes | |
| IR Distance | 30 ~ 50 m | |
| Ingress Protection | IP 67 | |
| Others | | |
| Power Supply | DC12V/PoE | |
| Power Consumption | < 9W | |
| Operating Environment | - 30°C ~ 60°C (-22°F~140°F) Humidity: less than 95 % (non-condensing) | |
| Dimensions (mm) | Φ 111.5 × 99.6 | |
| Weight (net) | Approx. 0.66KG | |
| Installation | Ceiling mounting (wall mounting available with the junction box andbracket) | |
| Certificate | CE, FCC | |
| Environmental Protection | Complies with Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006) | |

Specification are subject to change without notice. Hawk Vision is a registered trademark of AAA Security Solutions and its Overseas Subsidiary. All other trademarks belong to their respective owners. ©Copyright 2020 AAA Security Solutions. All rights reserved. Released 10/2020.

AAA SECURITY SOLUTIONS: 231, 2ND FLOOR KRISHNA MARKET, PITAMPURA, NEW DELHI-110034 SALES: 011-47097440 | SALES EMAIL: INFO@HAWKVISIONINDIA.COM | SUPPORT EMAIL: SUPPORT@HAWKVISIONINDIA.COM